



**PAVEMENT MARKING LEGEND:**

- ① 10 cm SOLID YELLOW LINE
  - ② 10 cm WHITE LINES AT 2.5 m APART  
80 cm WHITE STOP BAR  
1 m BETWEEN CROSSWALK AND STOP BAR
  - ③ 10 cm WHITE LINE, 25 m IN LENGTH, UNLESS SHOWN OTHERWISE  
10 cm WHITE LINE AT 3 m x 3 m CYCLE ARROWS AS SHOWN
  - ④ 80 cm YELLOW HATCHING AT  
7.5 m ON CENTRE, UNLESS SHOWN OTHERWISE
- DEVOTES PAVEMENT MARKING REMOVAL

**GENERAL NOTES:**

1. PAVEMENT MARKINGS SHALL BE PAINTED WITH THE EXCEPTION OF ARROWS, CROSSWALKS, STOP BARS AND LANE MARKINGS ON HULLMAR DRIVE WHICH ARE PERFORMED.
2. PREFORMED PAVEMENT MARKINGS SHALL BE APPLIED WITH COLD PLASTIC AND SHALL CONFORM TO THE REQUIREMENTS OF MT 89-41 AND OPS 774.
3. PAINTED PAVEMENT MARKINGS SHALL CONFORM TO THE REQUIREMENTS OF MT 89-41 AND OPS 774.
4. ALIGN NEW PAVEMENT MARKINGS TO EXISTING.
5. PROPOSED TRAFFIC SIGNS SHOWN ON PLAN ARE SUPPLIED AND INSTALLED BY TRANSPORTATION SERVICES.

REDUCTION OF DRAWING No. H-130-PM1



LOCATION  
 HULLMAR DRIVE BETWEEN  
 GODSFORD BOULEVARD AND YORK GATE BOULEVARD  
 MINOR ROAD IMPROVEMENT