Table 1: Traffic Calming Warrant Criteria

Atlas Avenue between Durham Avenue and Belvidere Avenue

Warrant	Criterion	Requirement		Met/Not Met
Warrant 1 Petition	1.1 Petition	A petition requesting traffic calming must be signed by at least 25% of households on the street. OR A direct request for the Ward Councillor. Warrants #2 and #3 will not be considered until Warrant #1 is satisfied.		Met – Undated petition received July 11, 2007
Impacts to Adjacent Streets		No significant traffic impacts on adjacent streets		Met –there should be no traffic spill- over to adjacent streets
Warrant 2 Safety Requirements (all three criteria must be fulfilled to satisfy this Warrant)	2.1 sidewalks	Continuous sidewalks on at least one side of the street (both sides for collector streets or higher classification). OR Where there are no sidewalks, the installation of sidewalk on at least one side of the street must have first been considered		Met – sidewalk on both sides of Atlas Avenue
	2.2 Road Grade	Road grade 5% or less OR Between 5% and 8% road grade may be considered. Investigation must determine installation to be safe.		Met – Road grade on Atlas Avenue is less than 5%
	2.3 Emergency Response	No significant Impacts on Emergency Services (as determined in consultation with Emergency Services (Fire, Ambulance and Police) staff.		TBD
Warrant 3 Technical Requirements (all four criteria must be fulfilled to satisfy this warrant)	3.1 Minimum Speed	85 th %ile speed is a minimum of 10 km/h (but less than 15 km/h) over a warranted 40 km/h speed limit, and the traffic volume requirements of Warrant 3.2 must be fulfilled. OR On streets where the 85 th %ile speed exceeds a warranted 40 km/h speed limit by a minimum of 15 km/h, there is no minimum volume required in warrant 3.2.		Not Met – Speed studies show 85 th percentile as 42 – 46 km/h
	3.2 Min. and Max. traffic Volume	Local Roads Traffic volume between 1,000 Veh/day and 8,000 Veh/day	Collector Roads Traffic volume between 2,500 Veh/day and 8,000 Veh/day	Met – Local Road with approx. 2900 vehicles b/n Durham & Belvidere Not Met – Local road with approx. 600 vehicles b/n Belvidere and Ava
	3.3 Minimum Street Segment Length between stop controls	Street segment length must exceed 120 meters between stop controls (signals or stop signs)		Met – there is at least 120 metres between the stop controls
	3.4 Transit Service	Impacts on regularly scheduled Toronto Transit Commission (TTC) services will not be significant (as determined in consultation with TTC staff)		Met – No TTC service

 $P:\ 2008\ Cluster\ B\ TRA\ Toronto\ and\ East\ York\ District\ TOP\ ts08020 te.top-AppA.doc-cag$