Appendix A

Table 1: Traffic Calming Warrant Criteria

Bingham Avenue, between Kingston Road and Gerrard Street East

Warrant	Criterion	Requirement		Met/Not Met
Warrant 1 Petition	1.1 Petition	A petition requesting traffic calming must be signed by at least 25% of households on the street. OR A direct request for the Ward Councillor. Warrants #2 and #3 will not be considered until Warrant #1 is satisfied.		Met – Request from Councillor
Impacts to Adjacent Streets		No significant traffic impacts on adjacent streets		Met – Low traffic volume on Bingham Avenue
Warrant 2 Safety Requirements (all three criteria must be fulfilled to satisfy this Warrant)	2.1 sidewalks	Continuous sidewalks on at least one side of the street (both sides for collector streets or higher classification). OR Where there are no sidewalks, the installation of sidewalk on at least one side of the street must have first been considered		MET – Sidewalks on both sides of Bingham Avenue
	2.2 Road Grade	Road grade 5% or less OR Between 5% and 8% road grade may be considered. Investigation must determine installation to be safe.		Met – Road grade less than 8%
	2.3 Emergency Response	No significant Impacts on Emergency Services (as determined in consultation with Emergency Services (Fire, Ambulance and Police) staff.		Not Met – TBD
Warrant 3 Technical Requirements (all four criteria must be fulfilled to satisfy this warrant)	3.1 Minimum Speed	 85th %ile speed is a minimum of 10 km/h (but less than 15 km/h) over a warranted 40 km/h speed limit, and the traffic volume requirements of Warrant 3.2 must be fulfilled. OR On streets where the 85th %ile speed exceeds a warranted 40 km/h speed limit by a minimum of 15 km/h, there is no minimum volume required in warrant 3.2. 		NOT MET – Speed studies show 85 th %ile as 45 km/h (June 12, 2009)
	3.2 Min. and Max. traffic Volume	Local Roads Traffic volume between 1,000 Veh/day and 8,000 Veh/day	Collector Roads Traffic volume between 2,500 Veh/day and 8,000 Veh/day	MET – Local Road with 1244 veh/day (June 12, 2009)
	3.3 Minimum Street Segment Length between stop controls	Street segment length must exceed 120 metres between stop controls (signals or stop signs)		Met
	3.4 Transit Service	Impacts on regularly scheduled Toronto Transit Commission (TTC) services will not be significant (as determined in consultation with TTC staff)		Met – No impact to TTC service

 $P:\label{eq:cluster} P:\label{eq:cluster} P:\labe$