

| Superseded/Cancelled (Remove) | | Revised/New (Insert) | | Drawings for Road Works |
|------------------------------------|----------|------------------------------------|----------|--|
| T No. | Revision | T No. | Revision | Remarks |
| All T- drawings | | | | Revision numbers to title block as follows: <ul style="list-style-type: none"> • Revision No. 0 means original release. • Revision No. 1 means first revision. • Revision No. 2 means second revision • Revision No. 3 means third revision and so on. |
| T-221.01 Nov 2014 | 0 | T-221.01 Apr 2015 | 1 | Asphalt Paving for Multi-Use Pathway <ul style="list-style-type: none"> • Topsoil or growing medium minimum depth revised to 125 mm from 100mm. |
| ---- | ---- | T-310.010-9 Apr 2015 | 0 | Concrete Boulevard Edge <ul style="list-style-type: none"> • New drawing. |
| T-310.020-2 Nov 2014 | 2 | T-310.020-2 Apr 2015 | 3 | Sidewalk Paved With Unit Paver Band at Curb <ul style="list-style-type: none"> • Thickness of paver revised to 70 mm from 60 mm to reflect industry standards and consistency with Streetscape Manual. |
| T-310.050-2 Nov 2014 | 3 | T-310.050-2 Apr 2015 | 4 | Vehicular Crossing of Sidewalk with Unit Paver Installation <ul style="list-style-type: none"> • Thickness of paver revised to 70 mm from 60 mm to reflect industry standards and consistency with Streetscape Manual. |
| T-509.010-1 Sheet 1 Nov 2014 | 1 | T-509.010-1 Sheet 1 Apr 2015 | 2 | Composite Pavement Patching For Utility Cuts <ul style="list-style-type: none"> • Note 2 revised. • Asphalt ledge of 300 mm added to drawing. |
| T-509.010-1 Sheet 2 Nov 2014 | 1 | T-509.010-1 Sheet 2 Apr 2015 | 2 | Flexible Pavement Patching for Utility Cuts <ul style="list-style-type: none"> • Asphalt ledge of 300 mm added to drawing. |
| T-560.040-1 Nov 2014 | 1 | ---- | ---- | Impressed Concrete Feature Strip <ul style="list-style-type: none"> • Drawing cancelled. This construction technique no longer used. |