

EXISTING OR NEW
CONCRETE CURB

EXPANSION JOINT,
6.0 m APART, TYP.

CONCRETE
SIDEWALK
COARSE TEXTURED
BROOM FINISH,
PERPENDICULAR
TO CURB, TYP.

CONCRETE
BOULEVARD EDGE
COARSE TEXTURED
BROOM FINISH,
45 DEGREE ANGLE
TO CURB, TYP.

CONTRACTION JOINT,
2.0 m APART, TYP.

EXPANSION JOINT WHEN
EXISTING SIDEWALK IS
RETAINED OR MONOLITHIC
SIDEWALK IS NOT FEASIBLE
(SEE NOTE 1)

TROWELLED
JOINTS, TYP.

CURB

STREET LINE..
(CONDITIONS VARY)

2.0 m, TYP.

6.0 m, TYP.

CONCRETE
BOULEVARD
EDGE
(VARIES)

SIDEWALK
(VARIES)

NOTE:

1. LONGITUDINAL EXPANSION JOINT IS REQUIRED BETWEEN THE SIDEWALK AND APRON WHEN THE DIFFERENCE BETWEEN THE SIDEWALK CROSSFALL AND THE APRON CROSSFALL IS 2% OR GREATER.
2. EXPANSION JOINT AND CONTRACTION JOINT ACCORDING TO T-310.010-1.
3. CONCRETE BOULEVARD EDGE THICKNESS AND BEDDING ACCORDING TO T-310.010-2.

All dimensions are in millimetres unless otherwise shown.

ENGINEERING & CONSTRUCTION SERVICES STANDARD DRAWING

REV 1

SEP 2017



CONCRETE BOULEVARD EDGE

T-310.010-9

NTS

SHEET 1