



NOTES:

1. PAVEMENT PATCH DIMENSIONS

- A) GENERALLY RECTANGULAR IN SHAPE.
- B) MINIMUM DIMENSION OF A PATCH BOUNDING A JOINT OR PAVEMENT EDGE SHALL BE 2.0m.
- C) MINIMUM DIMENSION OF AN INTERIOR PATCH SHALL BE 1.2m WITH A MINIMUM CLEARANCE FROM A JOINT OR PAVEMENT EDGE OF 1.2m.

2. ALL CONCRETE PAVEMENTS OTHER THAN ON LOCAL RESIDENTIAL STREETS AND UNLESS BOUNDED BY AN EXISTING PAVEMENT JOINT, SHALL HAVE PATCHES PROVIDED WITH ROAD TRANSFER BY INSERTING 25mm x 450mm EPOXY COATED DEFORMED TIE BARS SPACED AT 300mm CENTRES.

ON LOCAL RESIDENTIAL CONCRETE PAVEMENTS OR AT LOCATIONS SPECIFICALLY APPROVED BY THE COMMISSIONER, AGGREGATE INTERLOCK OR A FORMED KEY FOR LOAD TRANSFER ALONG THE EDGES OF THE PATCH MAY BE ALLOWED.

METRIC  
ALL DIMENSIONS SHOWN HERE ARE IN MILLIMETRES UNLESS OTHERWISE NOTED

APPROVED BY *Tom Denes*  
TOM DENES, P. ENG.  
EXECUTIVE DIRECTOR TECHNICAL SERVICES

SCALE N.T.S.



COMPOSITE PAVEMENT PATCHING

DATE: JUNE, 2001

REVISED:

STANDARD No. T-509.010-1