



TYPICAL COMPOSITE PAVEMENT SECTION

COMPOSITE PAVEMENT CLASSIFICATION	PAVEMENT THICKNESS
LOCAL COLLECTOR (BUS/TRUCK ROUTE)	50 mm SP 12.5 B, PG 64-28 200 mm PORTLAND CEMENT CONCRETE (PCC) 150 mm GRANULAR A
LOCAL COLLECTOR (NON BUS/TRUCK ROUTE)	50 mm SP 12.5 B, PG 64-28 150 mm PORTLAND CEMENT CONCRETE (PCC) 150 mm GRANULAR A

NOTES:

1. BRICK GUTTER WHERE SPECIFIED.
2. PAVEMENT THICKNESS SHALL BE ACCORDING TO CITY OF TORONTO PAVEMENT STRUCTURAL DESIGN MATRIX TABLE AS SHOWN ABOVE.
3. CONTRACTION JOINTS SHALL BE ACCORDING TO T-216.02-4.

All dimensions are in millimetres unless otherwise shown.

	ENGINEERING & CONSTRUCTION SERVICES STANDARD DRAWING	REV 3	SEP 2018
	COMPOSITE PAVEMENT CONSTRUCTION FOR LOCAL AND COLLECTOR ROADS	T-216.02-1	
		NTS	SHEET 1