



TYPICAL COMPOSITE PAVEMENT SECTION

COMPOSITE PAVEMENT CLASSIFICATION	PAVEMENT THICKNESS
MINOR ARTERIAL	40 mm SP 12.5 C, PG 64-28 50 mm SP 19.0 D, PG 64-28 250 mm PORTLAND CEMENT CONCRETE (PCC) 150 mm GRANULAR A
MAJOR ARTERIAL (See Note 4)	40 mm SP 12.5 FC2 D, PG 64-28 OR SP 12.5 FC2 E, PG 70-28 50 mm SP 19.0 D, PG 64-28 OR SP 19.0 E, PG 64-28 250 mm PORTLAND CEMENT CONCRETE (PCC) 150 mm GRANULAR A

NOTES:

1. PAVEMENT THICKNESS SHALL BE ACCORDING TO CITY OF TORONTO PAVEMENT STRUCTURAL DESIGN MATRIX AS SHOWN ABOVE.
2. SUBDRAIN SHALL BE ACCORDING TO T-216.02-8.
3. CONCRETE CURB AND GUTTER SHALL BE ACCORDING TO T-600.05-1.
4. PAVEMENT STRUCTURAL DESIGN MATRIX CAN BE USED AS A GUIDELINE.

All dimensions are in millimetres unless otherwise shown.

	ENGINEERING & CONSTRUCTION SERVICES STANDARD DRAWING	REV 3	SEP 2018
	COMPOSITE PAVEMENT CONSTRUCTION FOR MAJOR AND MINOR ARTERIAL ROADS		T-216.02-2
		NTS	SHEET 1