



STEEL ANCHOR HOOK BOLT FOR FLAT CONCRETE CURB

## DETAIL

## CROSS SECTION

### NOTES:

1. CONTRACTION JOINTS TO BE SAWCUT AND PLACED AT A MAXIMUM OF 6m SPACING AND/OR COINCIDE WITH EXISTING JOINTS IN CONCRETE ROAD BASE.
2. EXPANSION JOINTS TO BE CONSTRUCTED USING 12mm WIDE BITUMINOUS FIBER TO THE FULL THICKNESS OF THE CURBS.
3. ALL CONCRETE EXPOSED SURFACES FINISH, ACCORDING TO SPECIFICATION TS 3.50 (LIGHT BRUSH TEXTURE).
4. DEPTH OF CONCRETE TO MATCH THE DEPTH OF ASPHALT PAVEMENT PER PLAN.
5. FOR FLEXIBLE PAVEMENT, THE CONCRETE CURB TO SIT ON GRANULAR ROAD BASE AND REMOVE ANCHORS.

All dimensions are in millimetres unless otherwise shown.

ENGINEERING & CONSTRUCTION SERVICES STANDARD DRAWING

REV 0 SEP 2022



POURED IN PLACE FLAT CONCRETE CURB

T-603.041

NTS SHEET 1