



TRAIL USE	ACTIVITIES	PAVEMENT THICKNESS
LOW / MEDIUM	BIKING, ROLLER BLADING, SCOOTER, WALKING AND JOGGING. INFREQUENT MAINTENANCE/SERVICE VEHICLES.	80 mm SP 9.5 B, PG 58-28 (2 LIFTS) 150 mm GRANULAR A 200 mm 50 mm CRUSHED AGGREGATE
HIGH	FULL RANGE OF ACTIVITIES FROM WALKING TO BIKING. FULLSIZE VEHICLES, PICKUPS AND TRUCKS ARE EXPECTED IN REGULAR ACCESS.	40 mm SP 9.5 B, PG 58-28 60 mm SP 19.0 B, PG 58-28 150 mm GRANULAR A 200 mm 50 mm CRUSHED AGGREGATE

Note:

1. GRANULAR A CAN BE GRANULAR A NATIVE OR GRANULAR A RAP.
2. GRANULAR B TYPE II CAN BE USED IN LIEU OF 50 MM CRUSHED AGGREGATE.

All dimensions are in millimetres unless otherwise shown.



ENGINEERING & CONSTRUCTION SERVICES STANDARD DRAWING

REV 4

SEP 2021

**ASPHALT PAVING FOR
MULTI-USE PATHWAYS**

T-221.01

NTS

SHEET 1