



TWO-WAY STREET

GENERAL LAYOUT			
A*	NO. OF CUSHIONS	B**	C
7.5 m	3	0.55 m	0.5 m
8.0 m	3	0.6 m	0.7 m
8.5 m	3	0.85 m	0.7 m
9.0 m	3	1.0 m	0.8 m
9.5 m	3	1.05 m	1.0 m

LEGEND

- SPEED HUMP SIGN (WA-74)
- PRE-CUT THERMOPLASTIC PAVEMENT MARKINGS
- ① 10 cm SOLID WHITE LINE
- ② 10 cm SOLID YELLOW LINE

NOTES:

- A. WHENEVER POSSIBLE SIGNS SHOULD BE PLACED BACK TO BACK ON NARROW TWO-WAY STREETS.
- B. INSTALL THE ARROW AT THE CENTRE OF THE CUSHION.
- C. EXISTING CENTRELINE MARKING TO BE REINSTATED
- D. REFER TO THE SPEED CUSHION DRAWING (T-504.03) FOR 2 SETS OF SPEED CUSHIONS.
- E. REFER TO THE SPEED HUMP DRAWING (T-504.02) FOR THE SPEED CUSHION PROFILE.
- * IF THE EXISITING ROAD WIDTH EXCEEDS 9.5 m, TRANSPORTATION SERVICES SHOULD BE CONSULTED.
- ** IF PAVEMENT WIDTH FALLS BETWEEN THE WIDTHS IN COLUMN A, INTERPOLATION SHOULD BE APPLIED TO THE WIDTHS IN COLUMN B.

All dimensions are in millimetres unless otherwise shown.

	ENGINEERING & CONSTRUCTION SERVICES STANDARD DRAWING		REV 0	SEP 2024
	<p style="text-align: center;">SPEED CUSHIONS (3)</p>		T-504.04	
			NTS	SHEET 1